



TruBend Series 3000

Technical data



TruBend Series 3000

Bending machines

Technical data

| | TruBend 3066 | TruBend 3100 | TruBend 3170 |
|---|---------------------|---------------------|---------------------|
| PRESS FORCE | 660 kN | 1000 kN | 1700 kN |
| BENDING LENGTH | 2040 mm | 3060 mm | 4080 mm |
| WIDTH BETWEEN COLUMNS | 2364 mm | 3384 mm | 4404 mm |
| USABLE OPEN HEIGHT | 430 mm | 430 mm | - |
| USABLE OPEN HEIGHT FOR ENLARGED VERSION (OPTION) | - | 580 mm | |
| CONTROL TYPE | T3500T | T3500T | |
| USER INTERFACE | Multi-touch control | Multi-touch control | Multi-touch control |
| MAX. WORKING SPEED | 15 mm/s | 15 mm/s | |
| RAPID SPEED | 200 mm/s | 200 mm/s | |
| DIMENSIONS | | | |
| LENGTH | 2587 mm | 3607 mm | |
| WIDTH | 1644 mm | 1644 mm | |
| HEIGHT | 2370 mm | 2370 mm | |
| Y RAPID TRAVERSE | | | 190 mm/s |
| DIMENSIONS, WEIGHTS | | | |
| LENGTH | | | 4647 mm |
| WIDTH | | | 1644 mm |
| HEIGHT | | | 2925 mm |

Subject to changes. The details in our offer and order confirmation are definitive.